



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**



Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

98307353. 7

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

J. POTTE

DEN HAAG, DEN
THE HAGUE,
LA HAYE, LE

05/07/99

THIS PAGE BLANK (USPTO)



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

**Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation**

Anmeldung Nr.:
Application no.:
Demande n°: **98307353.7**

Anmeldetag:
Date of filing: **11/09/98**
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
Two Way TV Limited
London W4 5TW
UNITED KINGDOM

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
Delivering interactive applications

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:
Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:
H04L29/06, H04N7/24, A63F9/22

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

THIS PAGE BLANK (USPTO)

DELIVERING INTERACTIVE APPLICATIONS

The present invention relates to a method and apparatus for delivering an interactive application to a plurality of target platforms.

5 Interactive application providers employ skilled programmers to develop new interactive applications. Examples of such interactive applications are predictive games for use in conjunction with a live sporting broadcast, quiz games for use in conjunction with a live
10 quiz broadcast, on-demand quiz games (ie. not used in conjunction with a live quiz broadcast), home shopping applications and home banking applications.

With the rapid development of new target platforms for interactive services (each employing a broadcast network
15 with a different respective broadcast protocol) it is desirable to deliver the interactive applications over any chosen network in a simple and cost effective way. However conventionally this has been difficult because it has been necessary for the skilled programmers to take into account
20 the different broadcast protocols during development of the new application.

In accordance with a first aspect of the present invention there is provided a method of delivering an interactive application to a plurality of target platforms,
25 the method comprising

providing a set of application components;

converting the set of application components into a plurality of streams of broadcast data, each stream of broadcast data conforming with a respective target
30 platform; and

delivering each stream of broadcast data to its respective target platform.

In accordance with a second aspect of the present invention there is provided apparatus for delivering an
35 interactive application to a plurality of target platforms, the apparatus comprising

means for providing a set of application components;

a plurality of broadcast systems interfaces each converting the set of application components into a respective stream of broadcast data, each stream of broadcast data conforming with a respective target
5 platform; and

means for delivering each stream of broadcast data to its respective target platform.

Instead of having to provide multiple sets of application components (each set complying with a different
10 respective target platform) the invention allows the programmers to merely provide a single set of application components in any desired format, without needing to know anything about the ultimate target platforms. The broadcast system interfaces (BSIs) then convert the
15 application components shortly before, or during the broadcast.

The invention provides a convenient method of delivering an interactive application to a number of target platforms each having different requirements. For instance
20 the target platforms may comprise broadcast networks having different data protocols, formats or speeds. Alternatively the target platforms may comprise user interfaces with different memory capabilities etc.

The "open" architecture of the system enables new BSIs
25 to be added when the interactive application is to be delivered to a new target platform.

In the case where the application comprises a real-time application (eg a predictive game for use in conjunction with a live sporting broadcast) the method
30 typically further comprises manually inputting real-time application data;

converting the real-time application data into a plurality of streams of real-time broadcast data, each stream of real-time broadcast data conforming with a
35 respective target platform; and

delivering each stream of real-time broadcast data to its respective target platform.

The application components and/or real-time application data may be generated, converted and broadcast on-the-fly. However preferably the method further comprises storing the application components and/or real-time application data in a data store; and retrieving the application components and/or real-time application data from the data store before converting it into a stream of broadcast data.

A number of conversion steps may be necessary, including translating, substituting, selecting, time managing, or adapting for different data transmission mechanisms.

Provision may also be made for return path processing of return data (eg game-play input or home banking requests) from the target platforms.

An embodiment of the present invention will now be described with reference to the accompanying drawings, in which:

Figure 1 is a schematic functional diagram of an interactive service network;

Figures 2-4 illustrate examples of screen displays presented to an operator during preparation for a live football game;

Figures 5 and 6 illustrate screen displays presented to a remote player of the live football game;

Figure 7 is a schematic diagram illustrating two return data paths; and

Figure 8 is a schematic diagram illustrating the function of the Two Way TV engine.

Referring to Figure 1, the network comprises a central system 1 and a number of target platforms 2. Each target platform comprises a respective broadcast network 3 and user interface 4. The central system 1 is controlled by a central computer system (CCS) 5 which comprises a Sun SPARC binary file designed to operate UltraSPARC architecture workstations or servers (not shown). Although the CCS is

shown as a single unit it may be split into more than one binary file for performance and distributive requirements.

The CCS 5 communicates with a number of sub-systems 6 via a CCS text message gateway 7.

5 Authoring tools 8 include suitable tools (eg PCs) which are used by game programmers to develop new interactive applications. The interactive applications may all be very different but in general will include a number of application components such as executable program files,
10 bitmaps, sound samples, real-time data instructions, video clips, and other multimedia and data resources. When the new applications have been developed and tested, the game programmer logs on to a Windows NTTM based submit tool 9 which saves the application components in an application
15 database (not shown).

A number of previously saved applications are shown in Figure 1, namely six interactive, predictive games 10-15 for use in conjunction with a live sporting broadcast and a set of on-demand game engines 16.

20 A set of Universal Live Tools 17 (which include PCs running Windows NTTM based applications, and suitable input devices) are used by skilled operators to support the live applications 10-15.

25 A Mission Control system 18 (a Windows NTTM based application) is used by a system control officer to initiate application transmissions and manage real-time broadcasts.

30 An example of one of the interactive, predictive games (football 10) will be described below. The game is described in more detail in EP98302964.6. In the interactive football game, remote players are able to attempt to predict certain events prior to commencement of a live football match and can also attempt to predict certain events during the live broadcast.

35 Initially, prior to commencement of the live broadcast, the football application 10 is initiated by the system control officer using Mission Control 18, and an

operator uses the Live Tools 17 to set up certain predetermined information relating to the live broadcast for transmission to the user interfaces 4.

5 The operator is first presented with a screen as shown in Figure 2 in which he can select a home team and an away team from a list of such teams which have been previously stored in the application database. The operator can select the appropriate home and away teams and then click the OK button. This information is then stored in a Live
10 File store (not shown) associated with the Live Tools 17. The application database stores information relating to each team squad which will typically include more players than those actually selected to play the match. Shortly before commencement of the match, the actual team will be
15 announced and this information will be conveyed to the operator. The operator then causes the Live tools 17 to display all members of the squad of each team (Figure 3) allowing the operator to indicate which members of the squad have been picked to play and at the same time, he can
20 define the type of player, for example goalkeeper, attacker, midfield or defender. Once that information has been indicated, it is then stored in the Live File store.

The operator also sets up the particular types of event which can be predicted during the live broadcast. In
25 this example, these events include the time of the first goal, the time of the first booking etc. Examples of such events are indicated by the line of buttons at 50 in Figure 4.

Once all the information for the live broadcast has
30 been set up by the operator, a screen such as that shown in Figure 4 is displayed which at this time is inactive since the interactive game has not commenced. It will be noted, however, that the operator has been able to set up a significant amount of information in advance of the live
35 broadcast itself.

At the appropriate time, but before commencement of the football game, the operator will click the button 51

and the application will then be transmitted to the CCS 5 and broadcast to all the user interfaces 4 over the broadcast network 3 as discussed below. The following application components are broadcast:

- 5 1. Real-time data instructions such as "display copyright message at start of football game"; or "display [bit map] at half-time".
2. Executable computer code to be run by the user interfaces to implement the game.
- 10 3. Bit maps - eg. player faces, team logos etc.
4. Sounds - eg sampled referee's whistle or crowd noises.
5. Video clips, eg of individual players scoring a goal.
- 15 6. Team data - eg team names, player names and player positions.

The central system 1 is designed to be able to deliver applications on any target platform. Five target platforms are illustrated in Figure 1, each employing a different broadcast network, ie. NCI DTV Naviagator 20, OpenTV digital TV 21, MHEG-5 22, WebTV/WinCE 23 and PowerTV 24.

The system can also be expanded to handle any number of additional broadcast networks 25. Each broadcast network 20-25 has a respective different broadcast protocol. In order to deal with this problem, each target platform has an associated Broadcast System Interface (BSI) 26 which converts the set of application components associated with each application into a plurality of streams of broadcast data, each stream of broadcast data conforming with the broadcast protocol of its respective target platform. Thus when the operator clicks on button 51, the set of application components (ie. executable program files, bitmaps, sound samples, real-time data instructions, video clips etc.) are passed to the CCS 5 and then fed as parallel data streams to the BSIs 26 which convert the application components as appropriate prior to delivery over a respective broadcast network 3. The BSIs 26 are

previously encoded to make any necessary conversions in order to conform the data to their associated target platform. The conversion may (amongst others) include the following techniques:

5 **Translation**

This is the most basic data manipulation. Here the data is converted from an internal representation required by the authoring tools 8 into a representation appropriate to a respective broadcast protocol.

10 For example, a target platform may only receive ASCII text. In this case the BSI converts all data being transmitted from a binary representation to ASCII.

Translation takes place on a byte-to-byte basis and is the lowest level of transformation employed by the BSIs 26.

15 **Substitution**

In some cases the BSIs will replace application components with an alternative. This is similar to translation, except that substitution is normally done at a component level.

20 An example of this might take place where a game is being broadcast to two networks where the capabilities of the user interfaces 4 are different. The game being played contains a real-time video component that is delivered to the user interface 4 for display. On one network, the user
25 interface is not capable of storing the video component due to lack of memory and the BSI substitutes the video component with a set of still frames extracted from the video component. On another network the user interface is capable of storing the video component and the BSI delivers
30 the video component unchanged.

In another example a 16-colour bit map is to be delivered and one of the broadcast networks 3 or user interfaces 4 may only be able to support an 8-colour bit map. In this case the BSI converts the bit map into 8-
35 colour format on the fly prior to delivery.

Selection

In the case of selection, the BSI selects which application components to send or not to send. An example would be an application that contains three different binary files, one for a browser target platform, one for a target platform with an OpenTV broadcast network, and another for a target platform with a PowerTV broadcast network. The BSI associated with the OpenTV network would transmit the binary file for the OpenTV network, and ignore the others. The BSIs supporting the other target platforms behave in a similar way.

Timing

Different broadcast networks delivering the same programme are not necessarily temporally synchronised. Differences in timing may be up to one or two seconds, indeed set top boxes on different networks would generally have slight variances in their clocks, ie a box on one network may think that the time is 12:34.00 whilst a box on another network may believe it is 12:34.03. In addition to different networks having different clocks it is also a fact that different networks may not be broadcasting content at exactly the same time, ie a video program may start up to 1 or 2 seconds later on another network even though the clocks are the same.

In order to manage these anomalies between networks it is necessary for the BSI handling that network to compensate by introducing the required delay, either by delaying the broadcast of messages, or more appropriately by altering the timing information within messages.

Some networks do not provide a synchronised clock on all set top boxes. In these cases it is necessary for the BSI handling those networks to provide a clock message which the user interface may use to update its own synchronised clock.

Data Transmission Mechanisms

Different broadcast networks will probably use different techniques for transmission. Some may present a single large bandwidth download path for all data, some may

provide a high bandwidth mechanism for application components, and a smaller bandwidth mechanism for real-time data. In all of these cases the BSI will manage the different transmission techniques.

5 Exploring the above example in more detail, it is likely that a browser based architecture would provide some mechanism for providing application components from the service provider's server, using a carousel for example. In this scenario browser BSI would forward all game
10 components to the server to be placed on the carousel. The binary data messages would most likely be fed to the server which would then use IP tunnelling or similar to transmit the data to the user interfaces.

15 In the case of the MPEG-II system the BSI would produce MPEG-II transmit packets contains MPEG-II private data sections containing the binary data messages and the component downloads in a defined format.

20 The user interfaces 4 each include a Two Way TV engine 27 which decodes incoming data and presents it to an application processor 28 which runs executable program code and also incorporates suitable memory for storing data. Items 27,28 are typically provided in a set-top-box (STB) which is connected to a conventional home TV set. Alternatively items 27,28 may be part of a personal
25 computer. Although only a single user interface 27,28 is shown in Figure 1 with each broadcast network 20-25, it will be appreciated that each network 20-25 will broadcast to a large number of user interfaces.

30 In a commercial broadcast such as cable, satellite or the internet, the application processors 28 (in the form of set top boxes or personal computers) may have different capabilities. It is possible that the processors 28 may have different graphical abilities (such as colour depth, background mpeg and bitmap formats), different amounts of
35 RAM and differing audio capabilities.

It is not desirable to target the lowest capability processor only, as customers who have paid more for a more powerful decoder should reap the benefits.

Therefore in order to provide the highest quality of
5 interactivity on any given processor it is necessary to
create applications which can selectively use different
display models, colour depths, sounds and bitmaps. In
addition different sections of code may be used for
different processors. The Two Way TV engines 27 are able
10 to interrogate the capabilities of the application
processors 28 at runtime and dynamically decide which
components of the broadcast applications to utilise.

The function of the Two Way TV engines 27 is
illustrated in more detail in the example of Figure 8. In
15 this case a broadcast system interface 70 is encoded to
convert the application components into the format required
by an Open TV digital TV broadcast network 71. A second
BSI 72 converts the application components into the format
required by a PowerTV broadcast network 73. Two types of
20 user interface 74,75 are connected to the open TV network
71. User interface 74 includes an application processor 76
which can support 16-colour bitmaps. In contrast, user
interface 75 includes an application processor 77 which can
only support 4-colour bitmaps. The BSI 70 delivers 4-
25 colour and 16-colour bitmaps over the network 71. Each
user interface 74,75 has a respective Two Way TV engine
78,79. The engine 78 interrogates the application
processor 76 and determines that the processor can support
16-colour bitmaps, and so downloads the 16-colour bitmaps
30 on to the processor 76. In contrast, the engine 79
downloads the 4-colour bitmaps and discards the 16-colour
bitmaps.

Bitmaps are a relatively simple example, code modules
are more complex. For instance one type of user interface
35 may use a store and forward return path mechanism, whilst
another (on the same network) may use an instant access

step comprises broadcasting the stream of broadcast data to the application processor via the broadcast network.

8. A method according to claim 7 further comprising interrogating the application processor to determine the data capabilities of the application processor; and downloading data from the stream of broadcast data in accordance with the determined data capabilities of the application processor.

9. Apparatus for delivering an interactive application to a plurality of target platforms, the apparatus comprising means for providing a set of application components; a plurality of broadcast systems interfaces each converting the set of application components into a respective stream of broadcast data, conforming with a respective target platform; and

means for delivering each stream of broadcast data to its respective target platform.

CLAIMS

1. A method of delivering an interactive application to a plurality of target platforms, the method comprising providing a set of application components;

5 converting the set of application components into a plurality of streams of broadcast data, each stream of broadcast data conforming with a respective target platform; and

10 delivering each stream of broadcast data to its respective target platform.

2. A method according to claim 1 further comprising manually inputting real-time application data;

15 converting the real-time application data into a plurality of streams of real-time broadcast data, each stream of real-time broadcast data conforming with a respective target platform; and

delivering each stream of real-time broadcast data to its respective target platform.

20 3. A method according to any of the preceding claims further comprising storing the application components and/or real-time application data in a data store; and retrieving the application components and/or real-time application data from the data store before converting it into a stream of broadcast data.

25 4. A method according to any of the preceding claims wherein the step of converting comprises translating, substituting, selecting, time managing, or adapting for different data transmission mechanisms.

30 5. A method according to any of the preceding claims further comprising receiving and processing return data from one or more of the target platforms.

6. A method according to claim 5 wherein the application comprises a game and the return data comprises game-play input.

35 7. A method according to any of the preceding claims wherein each target platform comprises a broadcast network and an application processor, and wherein the delivering

operator clicks on an appropriate button and the information is then transmitted to the user interfaces 4.

During and/or after a game, the user interfaces 4 compare the associated player's predictions with the actual events. If the local player was successful in his prediction then the user interface 4 will indicate this to the player and will also pass that information via a suitable return path (eg the public switched telephone network) to the CCS 5 where it is handled by suitable return path processing 29.

An example of the return path processing 29 is illustrated in Figure 7. STB 30 is connected to a cable modem 31 which compresses the return data prior to transmitting it over a cable network to a cable service provider server 32. The return path processing 29 includes a decompressor 33 which decompresses the data into a form suitable for the CCS 5. STB 34 is connected to a modem 35 which transmits the return path data to a modem 36 in the return path handling system 29 over the conventional public switched telephone network (PSTN). Once the return data has been converted by the return path processing system 29, it is processed by the CCS 5 which provides standard scoring and voting facilities. For instance the users playing the football game may each have an individual score which is stored in a user database 30 and updated by the CCS 5 when the user makes a correct prediction. Alternatively the return path data may be used by the CCS 5 to register votes from the user interfaces. The return path processing facilities provided by the CCS may be augmented by a plug-in processing application 37. For instance a programmer can develop a new game which requires overall results or league positions to be broadcast back to the user interfaces and a suitable plug-in processing application 37 can be installed by the programmer. In some applications, however, return path communication with the CCS 5 is not necessary.

high bandwidth modem. Depending on which, the engine 27 would have to load and link the corresponding code module.

5 The Two Way TV engines 27,78,79 are generic items of code (i.e. the same engine is provided with each user interface). This enables the system to be easily expanded to deal with a new application processor 28 with different capabilities.

10 The engines 27,78,79 may either be previously provided in a user's personal computer or set-top-box, or may be broadcast over the broadcast network 3 before broadcast of the application components.

15 Returning to Figure 8, only a single type of user interface 81 is supported on network 73. In this case, the BS1 72 broadcasts 16-colour bitmaps only, and the engine 83 downloads the 16-colour bitmaps to the processor 82. Therefore in this case the engine 83 is effectively "transparent" as far as the 16-colour bitmaps are concerned.

20 When the application has been downloaded to the user interfaces 4, the interfaces display a screen similar to that shown in Figure 5. This indicates to the player the type of prediction which he can attempt. A comparison of Figures 4 and 5 will show that six of the events selected by the operator for prediction set out in the line 50 are
25 displayed on the display of Figure 5.

The remote player can then select one or more of the predictions. For example, if he selects the "Time Slot of First Goal", the screen shown in Figure 6 will be displayed which defines six different 15 minute periods during the
30 playing of a football game. The player can then indicate one of those periods, for example, the period 16-30 minutes, and this prediction is then stored in memory. In a similar way, the player can predict any one or more of the other items set out in Figure 5.

35 As the game develops, various events may or will occur. For example, when the first goal is scored, the

15

ABSTRACTDELIVERING INTERACTIVE APPLICATIONS

A method of delivering an interactive application to a plurality of target platforms (2). The method comprises

5 providing a set of application components;

converting the set of application components into a plurality of streams of broadcast data, each stream of broadcast data conforming with a respective target platform (2); and

10 delivering each stream of broadcast data to its respective target platform (2).

THIS PAGE BLANK (USPTO)




Fig. 1

Fig.2.

Choose Teams

All Teams

Home team

Define

Choose

Select teams

Ajax
Arsenal
Aston Villa
Barnsley
Belgium
Birmingham City
Blackburn Rovers
Blackpool
Bolton Wanderers
Bradford City
Bristol City

Away team

Define

Choose

OK

Cancel





Fig. 8








Fig. 7


24.48 GERMANY 1-1 ENGLAND

TIME OF FIRST GOAL


**IN WHICH TIME SLOT DO
YOU THINK THE 1ST
GOAL WILL BE SCORED**

0-15		16-30		31-45	 	46-60		61-75		76-90	
------	--	-------	---------------------------------------------------------------------------------------	-------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------	---------------------------------------------------------------------------------------	-------	--	-------	--


16




20



17



12



PREDICTIONS

Fig.6




Fig. 5

Match Time NOT CONNECTED [Connect!] Live Mode Pause Resume

Action Balls

Off 53 EVENT 54 SHOT 55 GOAL 56 CORNER 58 DENY 58 CLOCK 65

Predictions 52

Show

Final Score	Penalties	Log	First Goal	First Booked	First Faller	Half Time

Select First Scorer

Home	Number	Name	Away	Number	Name
1	Srnicek	1	Schmeichel		
4	Batty	2	G Neville		
5	Peacock	6	Pallister		
7	Lee	7	Cantona		
9	Shearer	8	Butt		
10	Ferdinand	10	Beckham		
11	Asprilla	15	Paborsky		
14	Ginola	16	Keane		

Your selection

No Goals Resolve

Fig. 4.

Fig.3.

Edit team

Arsenal

Squad

#	Player
06	Adams
07	Platt
08	Wright
11	Helder
13	Bartram
17	Hillier
20	Kiwomya
21	McGolderick
22	Selley
23	Dickov
24	Lukic
25	Marshall
26	Harper
27	Shaw
28	Hughes
29	Clark
30	Mcgowan
31	Rose

Number in squad 18

Edit squad

Team edit

>>Add>>

<<Remove<<

Start line up

#	Player
01	Seaman
02	Dixon
03	Winterburn
05	Bould
09	Merson
10	Bergkamp
12	Linighan
14	Keown
15	Parlour
16	Hartson
18	Morrow

U	G	D	M	A
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>

Substitutes

#	Player

U	G	D	M	A
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

Player type

U: undefined M: middle field

G: goal keeper A: attacker

D: defender

OK

Cancel